

TechCorro™[F] VCI Layflat Tubing

Details

"Lay-Flat" polythene tubing is a versatile packaging medium which lends itself to numerous applications. Supplied as one continuous polythene tube wound onto a roll. It can be sealed with heat sealers, ties, or tape. It is ideal for providing VCI and mechanical protection to irregularly shaped long objects or items where versatility is required to allow for packing a wide variety of objects of various sizes.

Metals protected

Detailed information on protected metals and compatibility issues can be found in our 'compatibility charts' that are available from our web site or our sales office.

Method of providing protection

VCIs emit small amounts of harmless active corrosion inhibitors. They are attracted to the charged surface of the metal. The flow of electrons in the metal and the flow of ions in the electrolyte surface are unable to operate and corrosion is halted. The length of protection depends on many factors and Technology Packaging staff are available to answer specific questions on corrosion protection or to provide detailed, objective proposals on suitable methods. This is true whether the problem relates to new projects or existing problematic transit and/or storage systems.



Sizes

Code	Open W (mm)	Length (m)	mu
1061000004	200	x 300	100
1061000005	250	x 300	100
1061000006	300	x 200	100
1061000007	400	x 200	100
1061000008	500	x 200	100

Handling & Storage information

Ideally the material should be kept cool, dry and protected from direct sunlight. It is preferable to keep it in its original wrapping when possible. If kept in these conditions the material will be effective for a minimum of three years.

This information is based on existing knowledge and it is not binding. No legal claims can be derived from it
10063-1810

The global partnership in corrosion prevention